LOUISIANA DEPARTMENT OF NATURAL RESOURCES OFFICE OF CONSERVATION INJECTION AND MINING DIVISION

RETURN TO → OFFICE OF CONSERVATION INJECTION AND MINING DIVISION 617 NORTH THIRD STREET BATON ROUGE, LA. 70802

	* TYPE OR PRIN SPECIAL INSTRUC	TALL ENTRIES * TIONS ON BACK			DATO	JN KOU GE, LA. 7080
W	WELL SERIAL NUMBER DATE		PATE	OPERATOR		CODE
WELL NAME & NUMBER				ADDRESS		
PARISH			CODE	CITY/STATE		
FIELD		CODE				
SE	SECTION TOWNSHIP RANG		RANGE	CONTACT PHONE		IONE
TI	EST REASON: □	NEW PERMIT-Appl N	No.	WORKOVER-Work Permit No.		
WELL CONSTRUCTION						
TO	TOTAL DEPTH PBTD		INJI	ECTION INTERVAL(S)		
TUBING DEPTH TUBING SIZ			ING SIZE	SIZE OF CASING BEING TESTED		
PA	ACKER DEPTH	PAG	CKER MAKE/MODEL			
MECHANICAL INTEGRITY PRESSURE TEST (MIPT)						
			I MIPT AT 500 PSIFC ORIZED SURFACE IN	R A MINIMUM OF 60 MINUTES JECTION PRESSURE PSI		
1	START TIME	INJECTION PRESSURE	ANNULUS PRESSURE	END TIME	INJECTION PRESSURE	ANNULUS PRESSURE
2	START TIME	INJECTION PRESSURE	ANNULUS PRESSURE	END TIME	INJECTION PRESSURE	ANNULUS PRESSURE
	☐ WELL INJECTING DURING TEST			☐ WELL SHUT-IN DURING TEST		
			CERTIF	TICATION		
OPERATOR REPRESENTATIVE				THIRD PARTY WITNESS		
I,				I,		

Form UIC-6

Signature _____

Signature_ Title ____

GENERAL INSTRUCTIONS

A mechanical integrity pressure test (MIPT) is required to be performed at the conclusion of a well workover or upon completion of a newly constructed or converted Class I injection or disposal well. The well operator is required to notify the Injection and Mining Division (IMD) at least 48 hours prior to performing a MIPT in order for a Conservation Enforcement Specialist (CES) to witness the test if possible. However, mechanical integrity pressure tests may be performed by a Class I well operator and documented on Form UIC-6 when a CES is not available to witness the test. Periodic operator performed MIPTs may also be reported on Form UIC-6.

A completed ORIGINAL Form UIC-6 must be submitted to the Injection and Mining Division within seven (7) days of test performance. For newly permitted wells, a <u>COPY</u> of Form UIC-6 must be submitted to IMD with the <u>Completion Report</u>.

All MIPTs reported on Form UIC-6 must be performed by the operator and witnessed by a third party who is not an employee of the operator.

NOTE: The performance of mechanical integrity tests on a Class I well by the operator in no manner exempts the operator from further testing of the well by a representative of the Office of Conservation.

MECHANICAL INTEGRITY PRESSURE TEST INSTRUCTIONS

Mechanical integrity pressure tests are to be performed with a standing column of fluid in the casing annulus from the top of the packer to surface. A minimum of 500 psi fluid pressure is to be applied to the casing annulus. A block valve is to be used to isolate the test pressure source from the test pressure gauge once the test has begun. All ports into the casing annulus, other than the one monitored by the test pressure gauge, are to be closed. The test pressure is to be monitored and recorded for a period of no less than 60 minutes. The test pressure gauge must be of sufficient sensitivity to indicate a loss of 5 percent, which is the maximum allowable test pressure loss during the testing period. Any loss of test pressure more than 5 percent during the minimum 60 minutes shall indicate a lack of mechanical integrity in the Class I well being tested. Any well which lacks mechanical integrity <u>must not</u> be put in service.

LIABILITY

The operator shall be held liable for any false, incorrect, and/or incomplete entry on this document and shall be subject to enforcement action and possible civil and/or criminal penalties as provided in LRS 30:17 and 18.

Form UIC-6 Rev 3/18